

# SMART CHARGER

SCharger-7KS-S0/SCharger-22KT-S0



Single-Phase

**7.4** kW/32 A  
SCharger-7KS-S0

Three-Phase

**22** kW/32 A  
SCharger-22KT-S0

\*Available in specific regions only



#### PV Power

Power Your Car with Solar  
Make EV Even Greener



#### Dynamic Charging Power

Automatic Detection and  
Adjustment  
No Worry about Overload



#### 3 Ways of Authentication

Authentication Through  
Bluetooth, RFID and APP



#### 3-Step Installation

Fast Installation in 15  
Minutes  
Wiring-free Maintenance

# **SCharger-7KS-S0/SCharger-22KT-S0** **Technical Specifications**

Technical Specification	SCharger-7KS-S0	SCharger-22KT-S0
<b>Inputs and Outputs</b>		
Charge power (configurable)	1.4 kW to 7.4 kW	1.4 kW <sup>1</sup> to 22 kW
Nominal voltage	230 V ± 20% (1-phase)	400 V ± 20% (3-phase)
Nominal current (configurable)	6-32 A (1-phase)	6-32 A (3-phase or 1-phase)
Nominal frequency	50 Hz/60 Hz ± 1 Hz	
Vehicle connection	Type 2 socket	
Cable cross-sectional area	Up to 10 mm <sup>2</sup>	
Network types	TN, TT, IT	TN, TT
<b>User Interface &amp; Communications</b>		
Protocol	Modbus TCP, OCPP 1.6	
Communication	Wi-Fi/Ethernet	
Charger status information	WRGB LED and app	
Authentication	RFID (ISO-14443-A), app, Bluetooth	
Remote control & monitoring	App	
Working mode	Normal Charge Scheduled Charge PV Power Preferred Next Trip <sup>2</sup>	
<b>Protection</b>		
Cable protection	Cable E-Lock via app	
Residual current protection (RCD)	Type A (30 mA) + DC 6 mA integrated	
Fire class	UL94	
Overcurrent protection	IEC 61851-1	
Over-temperature protection	Yes	
Surge protection	CAT II	
<b>General Specification</b>		
Operating temperature range	-35°C to +45°C	-35°C to +50°C @ 16A -35°C to +40°C @ 32A
Application environment	Outdoor/Indoor	
Storage temperature	-40°C to +70°C	
Relative humidity	5% ~ 95% RH	
Altitude	≤ 2000 m (derating between 2000~4000 m)	
Dimensions (H x W x D)	335 mm x 180 mm x 145 mm	
Weight	3 kg	3.1 kg
Installation mode	Wall-mounted	
IP rating	IP54	
Impact protection level	IK10	
Standby self-consumption	< 6 W	
<b>Standards Compliance (More Available Upon Request)</b>		
Safety & Health	EN IEC 61851-1 2019, EN 62311 2008, EN IEC 62311 2020, EN 50665 2017, EN 50364 2018	
EMC	EN IEC 61851-21-2 2021, EN 301 489-1 V2.2.3 2019, EN 301 489-3 V2.1.1 2019, EN 301 489-17 V3.2.4 2020	
Radio	ETSI EN 300 328 V2.2.2, ETSI EN300 330 V2.1.1	
RoHS	EN IEC 63000:2018	
<b>Others</b>		
Accessories	RFID Card * 2	

\*1 1.4 kW for 1-phase charging and 4. 2 kW for 3-phase charging

\*2 Next Trip mode is only available with EMMA-A02

Disclaimer: the preceding values are measured by an internal laboratory of Huawei in a specific environment. The actual values may vary with products, software versions, usage conditions, and environmental factors.